



**SHERWIN
WILLIAMS.**

105.13

PROMAR[®]
Exterior Acrylic Latex
Solid Color Stain
A16-300 Series

As of 12/01/2012, Complies with:			
OTC	Yes	LEED® 09 CI	N/A
SCAQMD	Yes	LEED® 09 NC	N/A
CARB	Yes	LEED® 09 CS	N/A
CARB SCM 2007	Yes	LEED® H	N/A
MPI #	16	NGBS	N/A

CHARACTERISTICS

ProMar Exterior Solid Color Acrylic Latex Stain is ideal for use on properly prepared, vertical wood, rough sawn lumber, textured or abraded plywood, siding shakes, and siding shingles.

May also be used on adjacent masonry and metal surfaces.

Featuring:

- 100% Acrylic
- Fast Application and Drying
- Good Penetration

Use on:

- Tract Housing
- Commercial Properties
- Apartments

Color: Solid Stain Colors
A sample brushout is recommended to ensure color satisfaction. Surface may darken slightly with application.

Coverage: 200-400 sq ft/gal
@ 4-8 mils wet; 1.3 - 2.6 mils dry

Depending on porosity and texture
Note: New wood normally requires less product than old, weathered wood. This is due to older wood being more porous than newer wood.

Drying Time, @ 77°F, 50% RH:
Touch: 1 hour
Recoat: 4 hours
Drying and recoat times are temperature, humidity, and film thickness dependent

Flash Point: N/A

Finish: 0-5 units @ 85°

Tinting with CCE:

Base	oz/gal	Strength
Extra White	0-5	100%
Deep Base	4-12	100%
Ultradeep Base	4-12	100%

Vehicle Type: Acrylic

A16W00351

VOC (less exempt solvents):
88 g/L; 0.73 lb/gal

Volume Solids: 31 ± 2%

Weight Solids: 47 ± 2%

Weight per Gallon: 10.7 lb

Mildew Resistant

This coating contains agents that inhibit the growth of mildew on the surface of this coating.

SPECIFICATIONS

Aluminum & Aluminum Siding
2 cts. ProMar Exterior Solid Color Stain

Block
1 ct. PrepRite Block Filler
2 cts. ProMar Exterior Solid Color Stain

Galvanized Steel
1 ct. All Surface Enamel Latex Primer
2 cts. ProMar Exterior Solid Color Stain

Masonry
1 ct. Loxon Masonry Primer
2 cts. ProMar Exterior Solid Color Stain

Bleeding Woods, Abraded Plywood, and Composition Board
1 ct. Exterior Oil-Based Primer
2 cts. ProMar Exterior Solid Color Stain

Other Woods — self-priming
2 cts. ProMar Exterior Solid Color Stain

Plywood — self-priming
2 cts. ProMar Exterior Solid Color Stain

Important: All stains tend to lap (dark lines where two freshly coated areas overlap). To minimize lapping:

- Do not stain in direct sun or on a hot surface.
- Always stain into a wet edge.
- Stain up and down vertical siding and across horizontal siding.
- Use two coats on badly weathered or unfinished wood.
- Apply a second coat when lap marks appear on the first coat.

SURFACE PREPARATION

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Existing peeled or checked paint should be scraped and sanded to a sound surface. Glossy surfaces should be sanded dull. Stains from water, smoke, ink, pencil, grease, etc. should be sealed with the appropriate primer/sealer.

Aluminum and Galvanized Steel
Remove any oil, grease, or other surface contamination. Remove all corrosion with sandpaper, steel wool, or other abrading method.

Masonry, Concrete, Cement, Stucco
All new surfaces must be cured according to the supplier's recommendations—usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with Loxon Masonry Primer.



**SHERWIN
WILLIAMS.**

PROMAR[®]
Exterior Acrylic Latex
Solid Color Stain
A16-300 Series

<u>SURFACE PREPARATION</u>	<u>APPLICATION</u>	<u>CAUTIONS</u>
<p>Remove any loose stucco, efflorescence, or laitance. Allow new stucco to cure at least 30 days before painting. If painting cannot wait 30 days, allow the surface to dry 5-7 days and prime with Loxon Masonry Primer. Repair cracks, voids, and other holes using an elastomeric patch or sealant.</p> <p>Woods, Plywood Sand exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth.</p> <p>Mill Glaze is a glossy finish on new, smooth sawn wood or on the peaks of some textured wood. Remove this by sanding to allow the stain to penetrate.</p> <p>Mildew Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution.</p> <p>Caulking Gaps between walls, ceilings, crown moldings, and other interior trim can be filled with the appropriate caulk after priming the surface.</p>	<p>Apply at temperatures above 50°F. No reduction necessary.</p> <p>Brush Use a nylon/polyester brush, or appropriate stain applicator.</p> <p>Roller Use a ½" - 1" nap synthetic roller cover.</p> <p>Spray—Airless Pressure..... 1800-2400 psi Tip..... .013"-.021"</p> <p><u>CLEANUP INFORMATION</u> Clean spills, spatters, hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using mineral spirits.</p>	<p>Protect from freezing. Non-photochemically reactive. For exterior use only. For vertical surfaces only. Not for use on roofs, decks, or other surfaces where water will accumulate. For wood decks and patios, use DeckScapes Solid Color Deck Stain</p> <p>LABEL CAUTIONS CAUTION contains CRYSTALLINE SILICA. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. HOTW 04/01/2013 A16W00351 05 00</p> <p>The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Sheet.</p>